

COOL-1300 / Q / QC

Cooled High Resolution Low-Noise
CCD Camera with 12-bit Digital-Output



Features

- 1280 (H) x 1024 (V) square pixels
- Peltier-cooled (- 20 °C)
- Progressive scan
- Interline-transfer sensor (IT)
- Exposure from 1/10000 sec. to 1000 sec.
- Camera dynamic: $\geq 1:2000$ (≥ 66 dB) COOL-1300
 $\geq 1:1800$ (≥ 65 dB) COOL-1300Q / QC
- Readout noise ≤ 13 e
- Dark current ≈ 0.1 e / pixel / sec.
- Digital RS-644 output with 12-bit
- C-mount compatible sensor size (2/3")
- Very compact design

VDS Vosskuhler

With a resolution of 1280 x 1024 effective pixels, the **COOL-1300** is a further member of the VDS high resolution CCD camera family. The **COOL-1300** is based on our CCD-1300 Low-Noise camera which has been extended by a peltier cooling in order to attain exposure times up to 1000 sec.

Due to the readout noise lower than 13 e and due to the very low dark current of approx. 0.1e/pixel/sec., the **COOL-1300** also achieves excellent signal to noise values at long exposure times.

The hermetic sealing of the vacuum section ensures an operation free of maintenance for many years.

Apart from long-time exposure the camera can also be operated at short exposures up to 1/10000 sec. By means of the progressive IT sensor the full resolution is always available.

With the switchable 2 x 2 binning function the light sensitivity can be increased four times.

The 2/3" sensor offers the possibility of using all C-mount lenses and optics customary in commerce. The camera is available with a b/w or color sensor (Bayer filter).

A further outstanding feature of the **COOL-1300** is the extremely compact construction which does not need a further control unit. Only a power supply customary in commerce with 12 V / 2.5 A for the supply of the camera is needed.

Technical Data

- Resolution: 1280 (H) x 1024 (V) pixels or 640 (H) x 512 (V) with 2 x 2 binning
- Progressive scan
- Pixel size: 6.7 μm x 6.7 μm ; 6.45 μm x 6.45 μm (Q-vers.)
- Active sensor size: 8.58 (H) mm x 6.86 (V) mm
8.26 (H) mm x 6.60 (V) mm (Q-vers.)
- Interline transfer sensor (no mech. shutter required)
- Optional: color sensor (Bayer filter)
- Long-time exposure up to approx. 1000 sec.
- Electronic shutter up to 1/10000 sec.; adjustable in 76 μs steps
- Image rate: up to 12.5 or 25 images/sec. with binning
- Dynamic: $\geq 1:2000$ (≥ 66 dB, for $t_{\text{exp}} \leq 60$ sec.)
 $\geq 1:1800$ (≥ 65 dB) (Q-vers.)
- Quantum efficiency: up to 50% at green
up to 70% at green (Q-vers.)
- Sensor saturation: ≥ 25000 e
- Readout noise ≤ 13 e
- Dark current: 0.1 e / pixel / sec.
- Cooling: - 20 °C regulated
(up to 25 °C environmental temperature)
- Forced air cooling
- Digital output: 12-bit, RS-644
- Pixel clock: 21 MHz
- Video gain: 1 or 2 (+ 6 dB)
- Power supply: + 12 V, max. 2.5 A
- Environmental temperature: 0° to 35° C
- Lens mount: C-mount
- CE standard
- Made in Germany

RS-644 Digital Output (37-pin D-SUB Jack)

Pin	Function	Pin	Function
1	PCLK	20	PCLK
2	LEN	21	LEN
3	FEN	22	FEN
4	D0 (LSB)	23	D0
5	D1	24	D1
6	D2	25	D2
7	D3	26	D3
8	D4	27	D4
9	D5	28	D5
10	D6	29	D6
11	D7	30	D7
12	D8	31	D8
13	D9	32	D9
14	D10	33	D10
15	D11 (MSB)	34	D11
16	GND	35	GND
17	TREX	36	TREX
18	SVZ	37	Mode
19	Binning Mode		

Power and Control Input (15-pin D-SUB Jack)

Pin	Function
1] + 12 V DC
2	
3] GND
4	
5	-
6	-
7	-
8	-
9	Mode: (Open) \Rightarrow Continuous Mode (GND) \Rightarrow Image on Demand
10	-
11	+] Trigger Input (Opto-Coupler)
12	-
13	+] Exposure Output (Opto-Coupler)
14	Line Sync Output (active low)
15	Frame Sync Output (active low)

